IBM SATA 1.8-inch and 2.5-inch MLC Enterprise SSDs for IBM System x

IBM Redbooks Product Guide

The IBM® SATA 1.8-inch and 2.5-inch MLC Enterprise solid-state drives (SSDs) for IBM System x® employ enterprise MLC NAND technology to bring an affordable, but performance-driven solution for applications requiring enterprise workloads with a mix of read-write operations. These industry standard 1.8-inch and 2.5-inch form factor SSD drives use a single-chip controller with a SATA interface on the system side and n-channels of NAND flash internally. They are targeted at databases and other enterprise workloads that require high I/O performance in random read and write operations including applications caching and tiering. The 1.8-inch SSDs can also be configured into the IBM eXFlash solution for maximum capacity and performance.

Figure 1 shows the IBM SATA 1.8-inch MLC Enterprise SSD.

Figure 1. IBM SATA 1.8-inch MLC Enterprise SSD

Did you know

IBM SATA MLC Enterprise solid-state drives for System x can be fully re-written up to eight times per day throughout their entire five-year life expectancy. These SSDs provide outstanding performance, endurance, reliability, and energy efficiency for both read- and write-intensive enterprise applications such as databases, data warehouses, corporate email and collaboration, actively connected users, medical imaging, and others.

Providing additional peace of mind, IBM SATA 1.8-inch and 2.5-inch Enterprise MLC SSDs are covered under IBM warranty. The drives carry a 1-year limited warranty, or when installed in an IBM System x server, these drives assume your system's base warranty.

Part number information

Table 1 lists the information for ordering part numbers and feature codes.

Table 1. Ordering part numbers and feature codes

Description	Part number	Feature code
2.5-inch SSDs		
IBM 100GB SATA 2.5" MLC HS Enterprise SSD	00W1125	A3HR
IBM 100GB SATA 2.5" MLC SS Enterprise SSD	00W1130	A3HS
1.8-inch SSDs		
IBM 100GB SATA 1.8" MLC Enterprise SSD	00W1120	A3HQ
IBM 200GB SATA 1.8" MLC Enterprise SSD	49Y6119	A3AN
IBM 400GB SATA 1.8" MLC Enterprise SSD	49Y6124	A3AP

The part numbers include the following items:

- One SSD without a drive tray (1.8-inch SSDs) or one SSD with a hot-swap or simple-swap drive tray (2.5-inch SSDs)
- Technical Update Flyer
- Warranty Flyer
- *Important Notices* document

Figure 2 shows the IBM SATA 2.5-inch MLC Enterprise SSD.

Figure 2. IBM SATA 2.5-inch MLC Enterprise SSD

Features

- Industry standard 1.8-inch or 2.5-inch form factors
- Support for standard 2.5-inch drive bay (2.5-inch SSDs) or eXFlash drive bay (1.8-inch SSDs) or SSD drive bay (1.8-inch SSDs) on selected System x, IBM iDataPlex®, IBM BladeCenter® and IBM Flex System™ servers
- Utilizes industry leading 24 nm MLC
- Cost-effective enterprise-grade MLC (eMLC) NAND technology
- MLC SATA drive with high read and write performance to fulfill client needs in the enterprise space
- High endurance, with up to six PB of total bytes written (TBW) to withstand applications with intensive read-write workloads
- Energy saving, with as little as 2.8 - 4.6 watt power consumption per drive
- Absence of moving parts to reduce potential failure points in the server
- Native command queueing (NCQ) with a queue depth of 32
- S.M.A.R.T. support
- Advanced Encrypting Standard (AES) 256-bit encryption
- Enterprise data path protection
- 55 bits per 512-byte sector ECC/EDC (BCH)
- Static wear leveling evenly distributes data across the drive
- Bad block management replaces failed blocks with new ones from the spare pool
- Performance throttling to ensure the lifetime expectation is met
- Power and thermal throttling to extend the life of the drive
- Data retention management to ensure availability and integrity of stored data
- Minimal write amplification for efficient flash utilization and extended life time

The key difference between Enterprise SSDs and Enterprise Value SSDs is their endurance (or life expectancy). SSDs have a huge but finite number of program/erase (P/E) cycles, which affects how long they can perform write operations and thus their life expectancy. Enterprise SSDs have significantly better endurance but higher cost/IOPS ratio compared to Enterprise Value SSDs. SSD write endurance is typically measured by the number of program/erase cycles that the drive can incur over its lifetime, listed as TBW in the device specification.

For example, with IBM 400 GB SATA 1.8-inch MLC Enterprise SSD, the entire 400 GB can be fully re-written up to eight times per day (more than 3 TB writes per day) to meet the five-year lifetime expectation of the drive, while the Enterprise Value SSD can only sustain up to 40 GB writes per day (75 times less) to provide the same five-year lifetime.

Technical specifications

Table 2 presents technical specifications for the IBM SATA MLC Enterprise solid-state drives.

Table 2. IBM SATA MLC Enterprise SSD technical specifications

Specification	100 GB			200 GB	400 GB
Part number	00W1120	00W1125	00W1130	49Y6119	49Y6124
Interface	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA
Hot-swap drive	Yes§	Yes	No	Yes§	Yes§
Form factor	1.8-inch	2.5-inch	2.5-inch	1.8-inch	1.8-inch
Capacity	100 GB	100 GB	100 GB	200 GB	400 GB
Endurance	5-year life time (1.5 PB TBW)	5-year life time (1.5 PB TBW)	5-year life time (1.5 PB TBW)	5-year life time (3 PB TBW)	5-year life time (6 PB TBW)
Data reliability	< 1 in 10^{18} bits read	< 1 in 10^{18} bits read	< 1 in 10^{18} bits read	< 1 in 10^{18} bits read	< 1 in 10^{18} bits read
MTBF	> 2,500,000 hours	> 2,500,000 hours	> 2,500,000 hours	> 2,500,000 hours	> 2,500,000 hours
IOPS read*	60,000	60,000	60,000	60,000	60,000
IOPS write*	40,000	40,000	40,000	40,000	40,000
Sequential read rate†	520 MBps	520 MBps	520 MBps	520 MBps	520 MBps
Sequential write rate†	500 MBps	500 MBps	500 MBps	500 MBps	500 MBps
Access time	< 0.1 ms	< 0.1 ms	< 0.1 ms	< 0.1 ms	< 0.1 ms
Shock	200 *g*, 10 ms 1500 *g*, 1 ms 1000 *g,* 0.5 ms	200 *g*, 10 ms 1500 *g*, 1 ms 1000 *g,* 0.5 ms	200 *g*, 10 ms 1500 *g*, 1 ms 1000 *g,* 0.5 ms	200 *g*, 10 ms 1500 *g*, 1 ms 1000 *g,* 0.5 ms	200 *g*, 10 ms 1500 *g*, 1 ms 1000 *g,* 0.5 ms
Vibration, operating	0.67 *g* rms 5-500 Hz	0.67 *g* rms 5-500 Hz	0.67 *g* rms 5-500 Hz	0.67 *g* rms 5-500 Hz	0.67 *g* rms 5-500 Hz
Vibration, non-operating	1.04 *g* rms 2-200 Hz	1.04 *g* rms 2-200 Hz	1.04 *g* rms 2-200 Hz	1.04 *g* rms 2-200 Hz	1.04 *g* rms 2-200 Hz
Typical power, reads	2.8 W	2.8 W	2.8 W	2.8 W	2.8 W
Typical power, writes	4.6 W	4.6 W	4.6 W	4.6 W	4.6 W

§ This SSD can be a hot-swap or non-hot-swap drive depending on the server in which it is installed.
* 4 KB block transfers
† 128 KB block transfers

The TBW value assigned to a solid-state device is the total bytes of written data (based on the number of P/E cycles) that a drive can be guaranteed to complete (% of remaining P/E cycles = % of remaining TBW). Reaching this limit does not cause the drive to immediately fail; the TBW simply denotes the maximum number of writes that can be guaranteed. A solid-state device will not fail upon reaching the specified TBW, but at some point after surpassing the TBW value (and based on manufacturing variance margins), the drive will reach the end-of-life point, at which time the drive will go into read-only mode. Because of such behavior by solid-state drives, careful planning must be done to use SSDs in the application environments to ensure that the TBW of the drive will not be exceeded prior to the required life expectancy.

Supported servers

The IBM SATA MLC Enterprise SSDs and supported RAID controllers can be installed in the System x and iDataPlex servers identified in Table 3 and the BladeCenter and Flex System servers identified in Table 4.

Table 3. Supported System x and iDataPlex servers (Part 1)

Part number	Product description	x3200 M3 (7327, 7328)	x3250 M3 (4251, 4252)	x3400 M3 (7378, 7379)	x3500 M3 (7380)	x3550 M3 (7944)	x3620 M3 (7376)	x3630 M3 (7377)	x3650 M3 (7945)	x3755 M3 (7164)	dx360 M3 (6391)
00W1120	IBM 100GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	N	N	N
00W1125	IBM 100GB SATA 2.5" MLC HS Enterprise SSD	Y	Y	Y	Y	Y	N	Y	Y	N	N
00W1130	IBM 100GB SATA 2.5" MLC SS Enterprise SSD	N	N	N	N	Y	N	N	N	N	Y
49Y6119	IBM 200GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	N	N	N
49Y6124	IBM 400GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	N	N	N

Table 3. Supported System x and iDataPlex servers (Part 2)

Part number	Product description	x3100 M4 (2582)	x3250 M4 (2583)	x3300 M4 (7382)	x3500 M4 (7383)	x3530 M4 (7160)	x3550 M4 (7914)	x3630 M4 (7158)	x3650 M4 (7915)	x3690 X5 (7147)	x3750 M4 (8722)	x3850 X5 (7143)	dx360 M4 (7912)
00W1120	IBM 100GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	Y	Y	Y	Y	N
00W1125	IBM 100GB SATA 2.5" MLC HS Enterprise SSD	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	N
00W1130	IBM 100GB SATA 2.5" MLC SS Enterprise SSD	N	Y	N	N	Y	N	N	N	N	N	N	Y
49Y6119	IBM 200GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	Y	Y	Y	Y	N
49Y6124	IBM 400GB SATA 1.8" MLC Enterprise SSD	N	N	N	N	N	N	N	Y	Y	Y	Y	N

Table 4. Supported BladeCenter and Flex System servers

Part number	Product description	HS12 (8028)	HS22 (7870)	HS22V (7871)	HS23 (7875)	HS23E (8038)	HX5 (7873)	x220 (7906)	x240 (8737)	x440 (7917)
00W1120	IBM 100GB SATA 1.8" MLC Enterprise SSD	N	N	Y	N	N	Y	N	N	N
00W1125	IBM 100GB SATA 2.5" MLC HS Enterprise SSD	N	Y	N	Y	Y	N	Y	Y	Y
00W1130	IBM 100GB SATA 2.5" MLC SS Enterprise SSD	N	N	N	N	N	N	N	N	N
49Y6119	IBM 200GB SATA 1.8" MLC Enterprise SSD	N	N	Y	N	N	Y	N	N	N
49Y6124	IBM 400GB SATA 1.8" MLC Enterprise SSD	N	N	Y	N	N	Y	N	N	N

See the IBM ServerProven® website for the latest compatibility information for System x, BladeCenter, iDataPlex and Flex System servers: http://ibm.com/servers/eserver/serverproven/compat/us/

Supported storage controllers

The IBM SATA MLC Enterprise SSDs require a supported disk controller. Table 5 lists the System x controllers that support these solid-state drives installed in a supported server. Table 6 lists the BladeCenter and Flex System controllers that support these solid-state drives installed in a supported server.

Table 5. RAID controllers for System x and iDataPlex servers supported with internal SSDs (Part 1)

Part number	Product description	x3200 M3 (7327, 7328)	x3250 M3 (4251, 4252)	x3400 M3 (7378, 7379)	x3500 M3 (7380)	x3550 M3 (7944)	x3620 M3 (7376)	x3630 M3 (7377)	x3650 M3 (7945)	x3755 M3 (7164)	dx360 M3 (6391)
81Y4492	ServeRAID H1110 SAS/SATA Controller	Y	Y	Y	Y	Y	N	N	Y	N	N
90Y4304	ServeRAID M5016 SAS/SATA Controller	N	N	N	N	Y	N	N	Y	N	N
46M0829	ServeRAID M5015 SAS/SATA Controller	Y	Y	Y	Y	Y	N	Y	Y	N	Y
46M0916	ServeRAID M5014 SAS/SATA Controller	Y	Y	Y	Y	Y	N	Y	Y	N	Y
46M0831	ServeRAID M1015 SAS/SATA Controller	Y	Y	Y	Y	Y	N	Y	Y	N	Y
46M0969	ServeRAID B5015 SSD Controller	N	N	N	N	Y	N	N	Y	N	N
49Y4731	ServeRAID-BR10il SAS/SATA Controller v2	N	N	N	N	Y	N	N	Y	N	N
46M0912	IBM 6Gb Performance Optimized HBA	Y	Y	Y	Y	Y	N	Y	Y	N	Y

Table 5. RAID controllers for System x and iDataPlex servers supported with internal SSDs (Part 2)

Part number	Product description	x3100 M4 (2582)	x3250 M4 (2583)	x3300 M4 (7382)	x3500 M4 (7383)	x3530 M4 (7160)	x3550 M4 (7914)	x3630 M4 (7158)	x3650 M4 (7915)	x3690 X5 (7147)	x3750 M4 (8722)	x3850 X5 (7143)	dx360 M4 (7912)
Onboard	ServeRAID M5110e SAS/SATA Controller	N	N	N	N	N	N	N	Y	N	Y	N	N
81Y4481	ServeRAID M5110 SAS/SATA Controller	N	N	Y	Y	Y	Y	N	Y	N	Y	N	Y
81Y4448	ServeRAID M1115 SAS/SATA Controller	N	N	Y	Y	Y	Y	N	N	N	Y	N	Y
81Y4492	ServeRAID H1110 SAS/SATA Controller	Y	Y	Y	N	Y	Y	N	N	N	N	N	Y
90Y4304	ServeRAID M5016 SAS/SATA Controller	N	N	N	N	N	N	N	N	Y	N	Y	N
46M0829	ServeRAID M5015 SAS/SATA Controller	Y	Y	N	N	N	N	N	N	Y	N	Y	N
46M0916	ServeRAID M5014 SAS/SATA Controller	Y	Y	N	N	N	N	N	N	Y	N	Y	N
46M0831	ServeRAID M1015 SAS/SATA Controller	Y	Y	N	N	N	N	N	N	N	N	N	N
46M0969	ServeRAID B5015 SSD Controller	N	N	N	N	N	N	N	N	Y	N	Y	N
Onboard	ServeRAID C105	N	N	N	N	N	N	N	N	N	N	N	N
Onboard	ServeRAID C100	N	N	N	N	N	N	N	N	N	N	N	N
46M0912	IBM 6Gb Performance Optimized HBA	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y

Table 6. RAID controllers for BladeCenter and Flex System servers supported with internal SSDs

Part number	Product description	HS12 (8028)	HS22 (7870)	HS22V (7871)	HS23 (7875)	HS23E (8038)	HX5 (7873)	x220 (7906)	x240 (8737)	x440 (7917)
90Y4390	ServeRAID M5115 SAS/SATA Controller	N	N	N	N	N	N	Y	Y	Y
90Y4750	ServeRAID H1135 Controller	N	N	N	N	Y	N	Y	N	N
Onboard	ServeRAID C105	N	N	N	N	N	N	N	N	N
Onboard	Integrated LSI SAS2004	N	N	N	Y	N	N	N	Y	Y
46C7167	ServeRAID-MR10ie (CIOv) Controller	N	N	N	N	N	N	N	N	N
Onboard	Integrated LSI SAS1064e	N	Y	Y	N	N	N	N	N	N
46M6908	SSD Expansion Card for IBM BladeCenter HX5	N	N	N	N	N	Y	N	N	N

See the IBM ServerProven website for the latest information about the adapters supported by each System x server type: http://ibm.com/servers/eserver/serverproven/compat/us/

Supported operating systems

Solid-state drives operate transparently to users, storage systems, applications, databases, and operating systems. The controllers that support SSDs are supported by the following operating systems:

- Microsoft Windows Server 2012
- Microsoft Windows Server 2008 R2
- Microsoft Windows Server 2008, Datacenter x64 Edition
- Microsoft Windows Server 2008, Datacenter x86 Edition
- Microsoft Windows Server 2008, Enterprise x64 Edition
- Microsoft Windows Server 2008, Enterprise x86 Edition
- Microsoft Windows Server 2008, Standard x64 Edition
- Microsoft Windows Server 2008, Standard x86 Edition
- Microsoft Windows Server 2008, Web x64 Edition
- Microsoft Windows Server 2008, Web x86 Edition
- Microsoft Windows Server 2008 Foundation
- Microsoft Windows Small Business Server 2008 Premium Edition
- Microsoft Windows Small Business Server 2008 Standard Edition
- Microsoft Windows Server 2003/2003 R2, Datacenter Edition
- Microsoft Windows Server 2003/2003 R2, Datacenter x64 Edition
- Microsoft Windows Server 2003/2003 R2, Enterprise Edition
- Microsoft Windows Server 2003/2003 R2, Enterprise x64 Edition
- Microsoft Windows Server 2003/2003 R2, Standard Edition
- Microsoft Windows Server 2003/2003 R2, Standard x64 Edition
- Microsoft Windows Server 2003, Web Edition
- Microsoft Windows Small Business Server 2003/2003 R2 Premium Edition
- Microsoft Windows Small Business Server 2003/2003 R2 Standard Edition
- Red Hat Enterprise Linux 6 Server Edition
- Red Hat Enterprise Linux 6 Server x64 Edition
- Red Hat Enterprise Linux 5 Server Edition
- Red Hat Enterprise Linux 5 Server Edition with Xen
- Red Hat Enterprise Linux 5 Server with Xen x64 Edition
- Red Hat Enterprise Linux 5 Server x64 Edition
- Red Hat Enterprise Linux 4 AS for AMD64/EM64T
- Red Hat Enterprise Linux 4 AS for x86
- SUSE LINUX Enterprise Server 11 for AMD64/EM64T
- SUSE LINUX Enterprise Server 11 for x86
- SUSE LINUX Enterprise Server 11 with Xen for AMD64/EM64T
- SUSE LINUX Enterprise Server 10 for AMD64/EM64T
- SUSE LINUX Enterprise Server 10 for x86
- SUSE LINUX Enterprise Server 10 with Xen for AMD64/EM64T
- VMware vSphere 5.1
- VMware vSphere 5
- VMware ESX 4.0
- VMware ESX 4.1
- VMware ESXi 4.0
- VMware ESXi 4.1

See the IBM ServerProven website for the latest information about the specific versions and service packs supported: http://ibm.com/servers/eserver/serverproven/compat/us/. Click **System x servers**, then **Disk controllers** to see the support matrix. Click the check mark that is associated with the System x server in question to see the details about operating system support.

Warranty

The IBM SATA 1.8-inch and 2.5-inch MLC Enterprise SSDs carry a 1-year, customer-replaceable unit (CRU) limited warranty. When installed in a System x server, these drives assume your system's base warranty and any IBM ServicePac® upgrade.

Physical specifications

The IBM SATA 1.8-inch MLC Enterprise SSDs have the following physical specifications.

Dimensions and weight (approximate):

- Height: 5 mm (0.2 in.)
- Width: 54 mm (2.1 in.)
- Depth: 79 mm (3.1 in.)
- Weight: 39 g (0.1 lb)

Shipping dimensions and weight (approximate):

- Height: 32 mm (1.3 in.)
- Width: 226 mm (8.9 in.)
- Depth: 150 mm (5.9 in.)
- Weight: 400 g (0.9 lb)

The IBM SATA 2.5-inch MLC Enterprise SSDs have the following physical specifications.

Dimensions and weight (approximate):

- Height: 9 mm (0.4 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)
- Weight: 99 g (0.2 lb)

Shipping dimensions and weight (approximate):

- Height: 63 mm (2.5 in.)
- Width: 174 mm (6.9 in.)
- Depth: 133 mm (5.2 in.)
- Weight: 448 g (1.0 lb)

Operating environment

The IBM SATA 1.8-inch and 2.5-inch MLC Enterprise SSDs are supported in the following environment:

- Temperature: 0 - 70 °C (32 - 158°F)
- Relative humidity: 8 - 85% (noncondensing)
- Maximum altitude: 3,050 m (10,000 ft)

Agency approvals

The IBM SAT 1.8-inch and 2.5-inch MLC Enterprise SSDs have the following agency approvals:

- UL
- CSA
- TUV
- FCC
- EMC
- CE Mark
- C-Tick Mark
- Taiwan (BSMI Certification)
- Korea EMI

Related publications

For more information see the following documents:

- IBM US Announcement Letter for 200 GB and 400 GB 1.8-inch MLC Enterprise SSDs
  http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS112-150
- IBM US Announcement Letter for 100 GB 1.8-inch and 2.5-inch MLC Enterprise SSDs
  http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS112-178
- IBM Redbooks® ServeRAID Adapter Quick Reference
  http://www.redbooks.ibm.com/abstracts/tips0054.html?Open
- *IBM System x Configuration and Options Guide*
  http://www.ibm.com/support/docview.wss?uid=psg1SCOD-3ZVQ5W
- IBM ServerProven
  http://ibm.com/servers/eserver/serverproven/compat/us/

Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service. IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing, IBM Corporation, North Castle Drive, Armonk, NY 10504-1785 U.S.A.

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you. This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk.IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you. Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products. This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurement may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs.

© Copyright International Business Machines Corporation 2012. All rights reserved.
Note to U.S. Government Users Restricted Rights -- Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

This document was created or updated on April 17, 2013.

Send us your comments in one of the following ways:

- Use the online **Contact us** review form found at:
  ibm.com/redbooks
- Send your comments in an e-mail to:
  redbook@us.ibm.com
- Mail your comments to:
  IBM Corporation, International Technical Support Organization
  Dept. HYTD Mail Station P099
  2455 South Road
  Poughkeepsie, NY 12601-5400 U.S.A.

This document is available online at http://www.ibm.com/redbooks/abstracts/tips0908.html .

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. These and other IBM trademarked terms are marked on their first occurrence in this information with the appropriate symbol (® or ™), indicating US registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the Web at http://www.ibm.com/legal/copytrade.shtml

The following terms are trademarks of the International Business Machines Corporation in the United States, other countries, or both:

BladeCenter®
IBM Flex System™
IBM®
iDataPlex®
Redbooks®
Redbooks (logo)®
ServerProven®
ServicePac®
System x®

The following terms are trademarks of other companies:

Linux is a trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.